



# GURTECH

Manufacturers of the Durable Range  
of **GGun** Lubrication Equipment

# G.Coupler

THE ORIGINAL

## GREASE GUN COUPLER

### **Spring Loaded Activation Trigger**

- Simply depress the trigger when locking the coupler onto the Zerk or to release the coupler when done.
- Easy clip-off, regardless of pressure build up in the line. **NO MORE** stuck couplers.
- No need to hold while greasing. Lock-on and free up both hands to operate your grease gun.

### **Sliding Sleeve**

Locks the coupler onto the Zerk.  
When you pump grease ... it stays on!



### **1/8" NPT Female Thread**

Standard size, fits most grease guns.



### **Four hardened spring steel jaws**

Resilient under high pressure.  
Fits all DIN and SAE specification Zerk  
grease nipples.

### **Leak Free, High Pressure Seal**

Patented design reduces leakage.

## Technical Specifications

Description	Specification
Max Pressure	10,000 psi (690 Bar)
Zerk Compatibility	Fits all DIN (Metric) and SAE specification Zerks (grease nipples).
Coupler Thread	1/8" NPT female thread.
Dimensions	L: 3 1/2 x W:
Diameter (front coupler)	31/32 in (16 mm). Fits most recessed Zerks (grease nipples).
Weight	4 oz (100 g)
Grease Gun Compatibility	Works with all grease gun types: pneumatic, manual and electric.
Seal	Durable nitrile rubber seal for longevity under high pressure.
Lock-on Mechanism	Four hardened spring steel jaws are resilient under high pressure.
Patents	WO 2011/069172